

Avansia

Avansia is a Retransfer technology card printer for very high quality card delivery.

Designed for rigorous use, Avansia is extremely robust and provides high security card issuance.

Capable of issuing more than 140 single-sided color cards per hour, it is ideal for card issuance in medium and large quantities.

THE PREMIUM RETRANSFER PRINTER FOR HIGH DEFINITION CARDS

Avansia is ideal for delivering:


- Corporate ID cards
- Secure access badges
- Student cards
- Payment cards
- Loyalty cards / gift cards
- National ID cards
- Driver's licenses

HOW DOES RETRANSFER TECHNOLOGY WORK?

The card is printed in two phases:

- 1 The card design is printed by dye sublimation on a transparent film.
- 2 The printed film is then fused to the card using a thermal bonding process for flawless results.

The built-in flattener applies pressure on the card, thus ensuring a perfectly flat surface.



FLAWLESS PRINTING

Retransfer technology (Reverse Transfer) maximizes print quality:

- High resolution 600 dpi: images and text are rendered perfectly and micro-text and watermarks are printed in high definition.
- Over the edge printing: this printer will guarantee that your edges print perfectly since the film fully covers the card.
- Evolis High Trust® consumables: their use provides flawless results.

MEDIA COMPATIBILITY

The Avansia Retransfer technology can print on all types of cards (PVC, PET, polycarbonate, ABS), including uneven card surfaces, such as smart contact and contactless cards.

The standard built-in card flattener delivers perfect results.

MULTIPLE ENCODING OPTIONS

To meet your specific needs, Avansia can be configured for all types of data encoding options: magnetic stripe, contact and contactless smart cards. These factory-configured encoding options can be combined.

INCREASED PRODUCTIVITY

Avansia is **exceptionally fast** with an output of more than **140 single-sided color cards per hour.**

Thanks to the high capacity feed tray and output tray (250 cards each) - and high capacity consumables (500 prints per roll), you can print your card runs with **no interruptions**.

MAXIMUM ENDURANCE

Designed to issue cards intensively, Avansia is robust and reliable. Its 3-year standard warranty and life time warranty on the print head guarantee your long-term investment.

Avansia can operate in **critical environments** (dust, heat...) thanks to its airtight structure.

ENHANCED SECURITY

Avansia can be easily locked by removing the RFID electronic key. This quite simply **prevents any attempt** to use the printer.

A mechanical key lock, available as an option, prevents access to consumables.

Moreover, Avansia comes with a **security slot** (Kensington® type).



Blank card storage in a removable card case with a capacity of 250 cards

and a status indicator

CERTIFICATIONS AND STATEMENT OF

COMPLIANCE

■ CE, FCC, UL, IEC

POWER SUPPLY

■ AC90-125V, 220-240V, 50/60Hz

OPERATING ENVIRONMENT

■ Humidity: 20% to 80% non-condensing

■ Min/max storage temperature: -20° / 60° C (-4° / 140° F)

SOUND (EVALUATED ACCORDING TO THE ISO 7779 STANDARD)

■ CD-ROM with printer drivers, user manuals and Quick Start

Sound pressure in assistant positions LpAm (color mode YMCK)

■ Storage humidity: 20% to 90% non-condensing

■ Min/max operating temperature: 10° / 30° C (50° / 86° F)

■ Operating ventilation: open air

■ When operating: 53 dB (A)

PACKAGING CONTENT

■ While waiting: 45 dB (A)

■ Cleaning materials

SIZE AND WEIGHT

■ Dimensions (H x W x D):

■ USB cable

■ Reject trav³

■ Power cord

Output hopper

■ Printe

■ RoHS

Flip-over module for dual-sided card personalization

Avansia

All encoders can be combined

■ Electronic key to secure the use of the printer



Personalized card storage in a removable output hopper with a capacity of 250 cards



GENERAL FEATURES

- Dual-sided printing (standard)
- Reverse transfer printing
- Over the edge printing
- Color dye sublimation and resin monochrome retransfer
- 600 dpi print head (23.6 dots/mm)
- Bitmap: 24 bits, R/G/B 256 level
- Printout: Y/M/C 256 level
- 64 MB of memory (RAM)

PRINTING PERFORMANCES¹

- - Single side (YMCK): 25 s/card 144 cards/hour
 - Dual side (YMCKK): 37.5 s/card 96 cards/hour

ADDITIONAL ENCODING MODULES

- Available modules
 - Magnetic stripe encoder ISO 7811
 - · Dual contact and contacless encoder
- Encoder connectivity: internal USB hub. 1 port available
- Encoding options can be combined
- Factory ordered

INTERFACES

- USB 2.0
- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led)

SAFETY

- RFID locking key
- Support for security lock (Kensington® type)
- Centralized locking system to secure access to blank cards, ribbon and film (optional)²

CARD MANAGEMENT AND SPECIFICATIONS

- Card feeder: 250 cards (0.76 mm 30 mil)
- Card output hopper: 250 cards (0.76 mm 30 mil)
- Reject tray capacity: 30 cards (0.76 mm 30 mil)³
- Card thickness: 0.76 mm (30 mil), manual adjustment
- Card types:
 PVC cards

 - Composite PVC cards
 - PET-F cards
 - PFT-G cards Polycarbonate cards
- ABS cards
- Card format: ISO CR80 ISO 7810 (53.98 x 85.60 mm 3.370" x 2.125")

EVOLIS HIGH TRUST® RIBBONS To maximize the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability,

- use Evolis High Trust® ribbons. ■ Ribbon capacity:
 - Clear and holographic: 500 prints/roll
 - YMCK: 500 prints/roll
 - YMCKK: 400 prints/roll
 - YMCKI (for smart cards and magnetic stripes): 400 prints/roll
 - YMCKH: 400 prints/roll
 - YMCFK (UV ink): 400 prints/roll

SOFTWARE

■ Compatible with Windows® XP SP2 32, Vista 32, W7 32/64 and W8 32/64

1 Time measured from the card's insertion detected by the sensor until the flip engine stops during ejection / 2 Option subject to approval from Evolis

- Two-line LCD display and LED status indicator
- Printer graphical notifications: empty input hopper, empty/low level ribbon alert...

3 Delivered with any printer including encoding option(s) / 4 Warranty subject to observance of specific conditions and use of Evolis High Trust® ribbons

EUROPE - MIDDLE-EAST - AFRICA

Evolis Card Printer - 14 avenue de la Fontaine - ZI Angers-Beaucouzé 49070 Beaucouzé - France

T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

AMERICAS - Evolis Inc. - Fort Lauderdale - evolisinc@evolis.com ASIA-PACIFIC - Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com

INDIA - Evolis India - Mumbai - evolisindia@evolis.com CHINA - Evolis China - Shanghai - evolischina@evolis.com

www.evolis.com



436 x 340 x 297 mm (17.16" x 13.38" x 11.69") ■ Weight: 20 kg (44.09 lbs) WARRANTY4

printers

22014 Eviol Scard Printer. All rights reserved. Actual productis) may differ from information contained in this document. All information, specifications or graphics are subject to change without prior notice. All trademarks mentioned herein belong to their respective owners. Pictures: Olivier Calvez, 07/2014. KB-AVA1-109-ENG-US and printer.